

# SAFETY DATA SHEET GRANATECH RANGE

| SECTION 1: Identification of    | the substance/mixture and of the company/undertaking  |
|---------------------------------|---|
| 1.1. Product identifier         |   |
| Product name                    | GRANATECH RANGE   |
| 1.2. Relevant identified uses   | of the substance or mixture and uses advised against  |
| Identified uses                 | High strength, low modulus mortar   |
|                                 |   |
| 1.3. Details of the supplier of |   |
| Supplier                        | PAREX Ltd   |
|                                 | Holly Lane Industrial Estate  |
|                                 | Atherstone  |
|                                 | Warwickshire  |
|                                 |   |
|                                 | Tel: +44 (0)1827 711755<br>(Mon-Fri 08:30-16:30)  |
|                                 | Fax: +44 (0)1827 711330   |
|                                 | sds@parex.co.uk   |
|                                 | Sus@parex.co.uk   |
| 1.4. Emergency telephone nu     | Imber   |
| Emergency telephone             | + 44 (0)1827 711755 (Mon-Fri 08:30 - 16:30)   |
| SECTION 2: Hazards identified   | cation  |
| 2.1. Classification of the subs | tance or mixture  |
| Classification (EC 1272/2008    | )   |
| Physical hazards                | Not Classified  |
| Health hazards                  | Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Skin Sens. 1 - H317 STOT SE 3 - H335 STOT SE 3 -<br>H335 |
| Environmental hazards           | Not Classified  |
| 2.2. Label elements             |   |
| Pictogram                       |   |
|                                 |   |
|                                 |   |
| Signal word                     | Danger  |
| Hazard statements               | H315 Causes skin irritation.  |
|                                 | H317 May cause an allergic skin reaction.   |
|                                 | H318 Causes serious eve damage  |

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

| Precautionary statements | <ul> <li>P264 Wash contaminated skin thoroughly after handling.</li> <li>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</li> <li>P501 Dispose of contents/ container in accordance with national regulations.</li> <li>P402+P404 Store in a dry place. Store in a closed container.</li> <li>Use within six months of date of manufacture.</li> </ul> |
|--------------------------|---|
| Contains                 | Portland Cement   |

2.3. Other hazards

SECTION 3: Composition/information on ingredients

| 3.2. Mixtures          |                      |        |
|------------------------|----------------------|--------|
| SILICA SAND            |                      | 30-60% |
| CAS number: 14808-60-7 | EC number: 238-878-4 |        |
| Classification         |                      |        |
| Acute Tox. 4 - H332    |                      |        |
| PORTLAND CEMENT        |                      | 10-30% |
| CAS number: 65997-15-1 | EC number: 266-043-4 |        |
| Classification         |                      |        |
| Skin Irrit. 2 - H315   |                      |        |
| Eye Dam. 1 - H318      |                      |        |
| Skin Sens. 1 - H317    |                      |        |
| STOT SE 3 - H335       |                      |        |

The full text for all hazard statements is displayed in Section 16.

# **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

| Inhalation  | Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention if any discomfort continues.   |  |
|---|---|--|
| Ingestion   | Immediately rinse mouth and drink plenty of water. If person becomes uncomfortable or if ingested in large amounts (50-100 ml for an adult person): Take to hospital along with these instructions. |  |
| Skin contact  | Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if symptoms are severe or persist after washing.  |  |
| Eye contact   | Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyelids widely. If irritation persists: Seek medical attention and bring along these instructions.  |  |
| Protection of first aiders  | First aid personnel should wear appropriate protective equipment during any rescue.   |  |
| 4.2. Most important symptoms and effects, both acute and delayed                |   |  |
| General information   | See Section 11 for additional information on health hazards.  |  |
| 4.3. Indication of any immediate medical attention and special treatment needed |   |  |
| SECTION 5: Firefighting measures  |   |  |

### 5.1. Extinguishing media

Suitable extinguishing media The product is not flammable. Use fire-extinguishing media suitable for the surrounding fire.

#### 5.2. Special hazards arising from the substance or mixture

#### 5.3. Advice for firefighters

Special protective equipment Use protective equipment appropriate for surrounding materials.

for firefighters

## SECTION 6: Accidental release measures

# 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet.

#### 6.2. Environmental precautions

**Environmental precautions** Do not discharge into drains, water courses or onto the ground.

#### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up Avoid generation and spreading of dust. Collect spillage for reclamation or disposal in sealed containers via a licensed waste contractor.

#### 6.4. Reference to other sections

**Reference to other sections** For waste disposal, see Section 13.

#### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

**Usage precautions** Avoid contact with skin, eyes and clothing.

Advice on general Do not eat, drink or smoke when using this product.

## occupational hygiene

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry, cool and well-ventilated place.

#### 7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

#### SECTION 8: Exposure Controls/personal protection

#### 8.1. Control parameters

#### Occupational exposure limits

#### SILICA SAND

Long-term exposure limit (8-hour TWA): 0.1 mg/m<sup>3</sup> Short-term exposure limit (15-minute): 0.1 mg/m<sup>3</sup> (Ireland)


#### PORTLAND CEMENT

Long-term exposure limit (8-hour TWA): WEL 4 mg/m<sup>3</sup> respirable dust Long-term exposure limit (8-hour TWA): WEL 10 mg/m<sup>3</sup> inhalable dust Long-term exposure limit (8-hour TWA): WEL 10mg/m3 (inh) 4mg/m3 (resp) (Ireland)

#### CALCIUM HYDROXIDE

Long-term exposure limit (8-hour TWA): WEL 1 mg/m3 (resp) 4 mg/m3 (resp) WEL = Workplace Exposure Limit

#### 8.2. Exposure controls





# **GRANATECH RANGE**

| Appropriate engineering<br>controls                        | As this product contains ingredients with exposure limits, process enclosures, local exhaust ventilation or other engineering controls should be used to keep worker exposure below any statutory or recommended limits, if use generates dust, fumes, gas, vapour or mist. |  |
|--|---|--|
| Eye/face protection  | Personal protective equipment for eye and face protection should comply with European Standard EN166.   |  |
| Hand protection  | Wear protective gloves.   |  |
| Other skin and body protection                             | Wear appropriate clothing to prevent skin contamination.  |  |
| Hygiene measures   | Wash at the end of each work shift and before eating, smoking and using the toilet.   |  |
| Respiratory protection                                     | If ventilation is inadequate, suitable respiratory protection must be worn.   |  |
| SECTION 9: Physical and Che                                | emical Properties   |  |
| 9.1. Information on basic physical and chemical properties |   |  |
| Appearance   | Powder.   |  |
| Colour   | Various colours.  |  |
| Odour  | Odourless.  |  |
| рН   | Approximately 12 - 13 in aqueous solution.  |  |
| Melting point  | Not applicable.   |  |
| Initial boiling point and range                            | Not applicable.   |  |
| Flash point  | Not applicable.   |  |
| Evaporation rate   | Not applicable.   |  |
| Flammability (solid, gas)                                  | Not applicable.   |  |
| Vapour pressure  | Not applicable.   |  |
| Relative density   | >1  |  |
| 9.2. Other information                                     |   |  |
| SECTION 10: Stability and rea                              | activity  |  |
| 10.1. Reactivity   |   |  |
| 10.2. Chemical stability                                   |   |  |
| Stability  | Stable at normal ambient temperatures and when used as recommended.   |  |
| 10.3. Possibility of hazardous reactions                   |   |  |

10.4. Conditions to avoid

## 10.5. Incompatible materials

10.6. Hazardous decomposition products

#### SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Skin corrosion/irritation

Human skin model test

### Serious eye damage/irritation

Serious eye damage/irritation Corrosivity to eyes is assumed.

Irritating.

Skin sensitisation

| Skin sensitisation   | Sensitising.  |  |
|--|---|--|
| Specific target organ toxicity - single exposure                         |   |  |
| Target organs  | Respiratory system, lungs   |  |
| Aspiration hazard  |   |  |
| Aspiration hazard  | May be harmful if swallowed and enters airways.   |  |
|  |   |  |
| Inhalation   | Irritating to respiratory system.   |  |
| Skin contact   | May cause an allergic skin reaction.  |  |
| Eye contact  | Causes serious eye damage.  |  |
| SECTION 12: Ecological I   | nformation  |  |
| 12.1. Toxicity   |   |  |
| 12.2. Persistence and deg  | jradability   |  |
| 12.3. Bioaccumulative pote   | ential  |  |
| 12.4. Mobility in soil   |   |  |
| Mobility   | The product is insoluble in water.  |  |
| 12.5. Results of PBT and   | vPvB assessment   |  |
| 12.6. Other adverse effect   |   |  |
| SECTION 13: Disposal co  | nsiderations  |  |
| 13.1. Waste treatment me   | thods   |  |
| General information  | Dispose of waste product or used containers in accordance with local regulations  |  |
| SECTION 14: Transport in   | nformation  |  |
| General  | Not classified as hazardous for transport.  |  |
| 14.1. UN number  |   |  |
| 14.2. UN proper shipping   | name  |  |
| 14.3. Transport hazard cla   |   |  |
| 14.4. Packing group  |   |  |
| 14.5. Environmental hazar  | rds   |  |
| 14.6. Special precautions for user                                       |   |  |
| 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code |   |  |
| SECTION 15: Regulatory information                                       |   |  |
| 15.1. Safety, health and en  | nvironmental regulations/legislation specific for the substance or mixture  |  |
| EU legislation   | Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16<br>December 2008 on classification, labelling and packaging of substances and mixtures (as<br>amended).<br>Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18<br>December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of |  |

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

## SECTION 16: Other information

Chemicals (REACH) (as amended).

| Issued by                 | QSHE Manager   |
|---------------------------|--|
| Revision date             | 30/08/2018   |
| Supersedes date           | 07/04/2017   |
| SDS number                | 20431  |
| Hazard statements in full | <ul> <li>H315 Causes skin irritation.</li> <li>H317 May cause an allergic skin reaction.</li> <li>H318 Causes serious eye damage.</li> <li>H332 Harmful if inhaled.</li> <li>H335 May cause respiratory irritation.</li> </ul> |

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.